



LLumar® Platinum Extra Paint Protection Film

LLumar® Platinum Extra paint protection film is for vehicle owners who want their finish to stand tough through the extreme driving conditions that come with track racing, gravel roads, off-roading, and harsh weather. It's virtually invisible, thicker than traditional paint protection film, and able to deliver chip-fighting, high-impact resistance. Ask for a full wrap of your entire vehicle, or have it installed in areas most vulnerable to damage such as rocker panels, fenders, hoods, bumpers, and doors.



Self-healing protection

Self-heals surface scratches with heat, offering protection against rocks, road debris, winter salt and sand



Advanced water resistant surface

Our hydrophobic, water-beading HydroGard™ technology provides stain resistance and enhanced durability



Hard-wearing defense

Our highest impact resistance in a thicker, stronger PPF made for gravel roads, track racing, and harsh weather



Manufacturer's 10 year limited warranty¹

A 10-year manufacturer's limited warranty¹ covers your investment in gloss finish LLumar Platinum PPF so you can wash, wax, and drive your vehicle worry-free

LLumar® Platinum Extra Paint Protection Film



Physical property	Standard Test Method	Performance
Chemical Resistance	ASTM D7244/D6279 Isopropyl Alcohol	No Detrimental Effect (after 100 cycles)
Chemical Resistance	ASTM D7244/D6279 MEK	No Detrimental Effect (after 100 cycles)
Weathering	ASTM D7869	No Detrimental Effect (after 5000hrs)
Rock Chip Resistance	SAE J400/ ASTM D3170	Pass
Thickness Range		10.6-11.6mil (269 - 295 µ)

All statements, technical information and recommendations herein are based on tests the manufacturer believes are reliable. The manufacturer does not warrant or guarantee the accuracy or completeness of this information.

Application and storage

Recommended installation environment temperature should be within 15.5°C – 32°C	Recommended installation solution (tack solution): 20% of 99.9% isopropyl alcohol diluted with 80% distilled water	Required product storage conditions of 15.5°C – 32°C
---	--	--

Multiple roll sizes are available for this product. For more information, contact your LLumar representative.



*Certain restrictions apply; see dealer for warranty details. ©2023 Eastman Performance Films, LLC. All rights reserved. No liability is accepted for errors. 01/23.
Check local tint laws.

