



LLumar® Select Black Paint Protection Film

Most paint protection film is designed to enhance durability and blend in with your finish – but not LLumar® Select Black PPF. It's a premium PPF that changes the look of any underlying colour to a rich, glossy black. It offers tough protection and lots of customisation opportunities in a single product. Go for a full wrap, stripes, accents on mirrors, spoilers, or the hood. The choice is yours. Whatever style you choose, you can be sure your new look will get the attention it deserves.



Self-healing protection

Self-heals surface scratches with heat, offering protection against rocks, road debris, winter salt and sand



Advanced water resistant surface

Our hydrophobic, water-beading HydroGard™ technology provides stain resistance and enhanced durability



Restyle and protect with just one installation

Select Black Paint Protection offers durability and looks with just one upgrade



Manufacturer's 10 year limited warranty¹

A 10-year manufacturer's limited warranty¹ covers your investment in gloss finish LLumar PPF so you can wash, wax, and drive your vehicle worry-free

LLumar® Select Black

Paint Protection Film



Physical property	Standard Test Method	Performance
Chemical Resistance	ASTM D7244/D6279 Isopropyl Alcohol	No Detrimental Effect (after 100 cycles)
Chemical Resistance	ASTM D7244/D6279 MEK	No Detrimental Effect (after 100 cycles)
Weathering	ASTM D7869	No Detrimental Effect (after 5000hrs)
Rock Chip Resistance	SAE J400/ ASTM D3170	Pass
Thickness Range		7.7-7.9mil (195,6 – 200,6 μ)

All statements, technical information and recommendations herein are based on tests the manufacturer believes are reliable. The manufacturer does not warrant or guarantee the accuracy or completeness of this information.

Application and storage

Recommended installation environment temperature should be within 15.5°C – 32°C	Recommended installation solution (tack solution): 20% of 99.9% isopropyl alcohol diluted with 80% distilled water	Required product storage conditions of 15.5°C – 32°C
---	--	--

Multiple roll sizes are available for this product. For more information, contact your LLumar representative.



¹Certain restrictions apply; see dealer for warranty details. ©2023 Eastman Performance Films, LLC. All rights reserved. No liability is accepted for errors. 01/23.
Check local tint laws.

WWW.LLUMAR.COM/EMEA
FOLLOW LLUMAR ON

